

Advanced Wood Paint, LLC

MATERIAL SAFETY DATA SHEET

Effective Date: 01/03/2014

SECTION I: PRODUCT GROUP AND COMPANY INFORMATION

Product Name: Stainable Primer
Product Group: Latex Primer

Manufacturer: Advanced Wood Paint, LLC
10443 Old Atlanta Highway
Covington, GA 30014
770-283-0098

SECTION II: HAZARDOUS INGREDIENTS

Material	Wt.%	TLV	CAS NO.
Latex	45.4	10mg/m ³	9003-20-7
TiO ₂	18.2	10mg/m ³	13463-67-7
Silica, amorphous	20	10mg/m ³	7631-86-9

SECTION III: PHYSICAL CHARACTERISTICS

Boiling Point: Approximately 212⁰ F
Freezing Point: 32°F
Appearance and Odor: White Liquid with acrylic odor
Specific Gravity: 1.32
Melting Point: N/A
Percent Volatile: 54.9%

SECTION IV: HEALTH HAZARD DATA

SKIN CONTACT: Wash with soap and water at end of work period. If skin rash occurs, discontinue use and see physician.

EYE CONTACT: Wash immediately with water (minimum 15 minutes) and seek medical attention to avoid lasting effects.

INHALATION: Breathing of dust or spraying mist may cause irritation to the eyes, nose, throat, or upper respiratory system. If this occurs, seek fresh air immediately.

INGESTION: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

HAZARDOUS MATERIAL INFORMATION SYSTEM (HMIS) RATINGS:

1	HEALTH
0	FLAMMABILITY
0	REACTIVITY
1	PROTECTIVE EQUIPMENT

0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe

SECTION VI: REACTIVITY DATA

INCOMPATIBILITY: None known
STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur

SECTION VII: PRECAUTIONS FOR SAFE HANDLING

- *Slippery when wet. Remove excess material and wash area with water.
- *Dispose of materials in landfill in accordance with Federal, State and local regulations.

SECTION VIII: CONTROL MEASURES

- *Wear NIOSH/MSHA approved respiratory device when spraying.
- *Ventilate by general mechanical or local exhaust.
- *Wear safety goggles when spraying.