### COMMANDER Omni Fiberglass Antenna, 865-900, 12.1dBi, N Female

Please visit us on the internet at <a href="http://www.commandertech.com">http://www.commandertech.com</a>

## **Product Description**

These center-fed collinear antennas ensure consistent gain and impedance across the operating frequency band and are specifically designed to meet various omnidirectional requirements for mobile radio services in the 806-960 MHz bands. Copper alloy radiating elements are encased in a weatherproof fiberglass low loss housing and permanently attached to a 6061-T6 aluminum support pipe.

10017 SERIES

#### Features/Benefits

- Fiberglass construction protects radiating elements in hostile environments - Copper radiating elements minimize possible generation of intermod products - Center-fed design eliminates beamswing across the band

_						ca					•						
		•	-	1	m	~	7	7	О.	$\sim$	IJ	7	v	 7	^	м	•
	•	ч.	71		ı v	-T-I	-,	• 1	_	•			T	 ш	•,		-

Frequency Band	824-894 MHz
Horizontal Pattern	Omni Directional
Antenna Type	Fiberglass Omni
Electrical Down Tilt Option	Fixed
Gain, dBi (dBd)	12.1 (10)
Frequency Range, MHz	865-900
Connector Type	N Female
Connector Location	Bottom
Mounting Type	Fixed
Electrical Down Tilt, deg	0
Orientation	Upright
Mounting Hardware	46 Clamp Set
Rated Wind Speed, km/h (mph)	160 (100)
Gain (Omni), dBi (dBd)	12.14 (10)
VSWR	< 1.5 : 1
Vertical Beamwidth, deg	6
Polarization	Vertical
Maximum Power Input, W	500
Lightning Protection	Direct Ground
Flexible Extensions	Optional
Impedance, Ohms	50
Overall Length, m (ft)	4.29 (14.06)
Element Housing Length, m (ft)	3.68 (12.06)
Mounting Pipe Diameter, m (in)	0.07 (2.75)
Support Pipe Length, m (ft)	0.61 (2)
Weight, kg (lb)	11 (24)
Radiating Element Material	Copper
Element Housing Material	Fiberglass
Support Pipe Material	Aluminum Alloy
Max Wind Loading Area m <sup>2</sup> (ft <sup>2</sup> )	0.177 (1.91)
Survival Wind Speed, km/h (mph)	200 (125)
Bend Mom @ Rated Wind 1" Below Pop of Mt Pipe, N m (ft lbf)	633 (467)
Wind Load - Side @ Rated Wind, N (lbf)	338 (76)
Shipping Weight, kg (lb)	20.4 (45)
Packing Dimensions, HxWxD mm (in)	4940 x 100 x 100 (194.48 x 3.94 x 3.94)
Packing Dimensions, HxWxD, m (ft)	4.94 x 0.1 x 0.1 (16.2 x 0.33 x 0.33)
Shipping Mode	Common Carrier

## **Notes**


				_
COMMANDER Model 10017-4	DE\/· 1 0	Print Date:	6/11/2012	
COMMANDER Model 10017-4			0/11/2012	




COMMANDER Omni Fiberglass Antenna, 865-900, 12.1dBi, N Female

Please visit us on the internet at <a href="http://www.commandertech.com">http://www.commandertech.com</a>

# **Other Documentation**





All information contained in this datasheet is subject to confirmation at time of ordering