



# **Anvil Quik Plast Drywall Surfacer 1810**

Interior Dry Wall  
**1810**

Level 5 Flat Finish

#### **DESCRIPTION AND FEATURES:**

**Anvil Quik Plast Drywall Surfacer** is a specially formulated interior drywall primer that ensures the finish coat of flat paint will look it's best. #1810 covers and fills the differences between the texture variations of gypsum board paper and joint compound finishes. It helps to equalize the rough, uneven, and minor surface imperfections found in new construction dry wall installations. **Anvil Quik Plast** forms a tight smooth film with is excellent for use under flat wall paints. For excellent hold out of semi-gloss and stain finish coats, use **Anvil 1st Kote 1815** or **Anvil Top Hat High Build Surfacer 1820**.

#### **USES:**

**Anvil Quik Plast Drywall Surfacer** is used on interior new construction drywall, cured plaster or concrete surfaces. The prime finish produced by this product is excellent for walls in residential construction, hotels, motels, offices and apartments that require a uniform flat painted finished wall appearance.

#### **SURFACE PREPARATION:**

Substrate must be clean, dry, sound and PAINT READY. Wall surfaces should be free of dust, grime or other contaminates that could interfere with the bonding characteristics of **Anvil Quik Plast**. Product, air and surface temperatures must be maintained at a minimum of 50 F. New masonry or plaster must be allowed to cure for at least thirty days. Repair any significant voids, cracks and fastener holes. Check all corner beads or exposed nail and screw heads that are likely to produce rust in the future and prime with a stain blocking metal primer. On walls stained from mildew, water, grease or other causes, a stain blocking primer should be applied to reduce flashing and bleed through.

#### **COVERAGE:**

Coverage will vary greatly depending upon method of application, surface condition and technique employed by the applicator. A test application is recommended to determine actual coverage under specific job conditions. Average coverage 150 square feet per gallon.

#### **APPLICATION:**

Apply by a suitable airless spray unit at package consistency. The airless sprayer should be capable of delivering more that 3/4 gallon a minute. Use a 3/8" material hose and a 21 to 23 tip at the lowest psi to achieve uniform atomization, approximately 2000 to 2600 psi. Always work to a wet edge and achieve full coverage by overlapping preceding application with a 1/4 to 1/2 fan width at a 18" distance from surface. Varying orifice size, pressure and technique will have an effect on actual coverage. Use a clean or new material hose to avoid previously sprayed dry paint chips from releasing and clogging tips. Topcoat when dry.

#### **CLEAN UP:**

Clean up immediately after use with warm, soapy water. Dried material is extremely difficult to remove.

#### **Limitations:**

Do not apply when the temperature is below 55°F or when relative humidity is above 90%. Ambient temperature must be 5° above the dew point and rising. Do not apply to surfaces with excessive moisture content, not exceeding 22% moisture. Shelf-life is 12 months when stored between 50°F and 80°F. When using, do not keep in direct sunlight for prolonged periods. Close container after each use. Not formulated as a finish coat, must be top coated with flat paint.

**KEEP FROM FREEZING.**

#### **TECHNICAL DATA:**

**Color: White, may be tinted.  
up to 4oz. Universal Colorant**

**GENERIC TYPE: Vinyl Acrylic**

**GLOSS: Matte**

#### **SOLID CONTENT:**

**BY WIEGHT: 65.58  
BY VOLUME: 34.42**

**%PIGMENT BY WEIGHT: 59.01**

**%VEHICLE BY WEIGHT: 6.52**

**VISCOSITY: 108 Ku**

**WEIGHT PER GALLON: 13.39 lbs.**

#### **AVERAGE COVERAGE:**

**150 square feet per gallon**

#### **DRYING TIME @ 77 F, 50% RH:**

**Touch—1/2 to 1 hour**

**Top coat—2 hours**

**CLEANUP: Clean all equipment immediately  
after use with warm soapy water.**

**THINNING: Not recommended**

**VOC: 94.4 grams/liter**

**AVAILABLE IN 5 GALLON PAILS**

Revised 1-09 Supersedes all prior publications  
GRO

Page 1 of 2

WARNING! WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! IRRITANT! HARMFUL IF SWALLOWED. IF TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID; if you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.