



# ULTRASEAL CONCRETE FLOOR & DRIVEWAY CLEAR SEALER



## 1330

AVAILABLE SIZES  
1 GALLON CAN  
5 GALLON PAIL

RESIN: 100% Acrylic

COLOR: Clear

SOLIDS BY WEIGHT: 33.0%

SOLIDS BY VOLUME: 30.0%

VISCOSITY: 78KU@75F

WEIGHT PER GALLON:  
9.45lbs.

FLASH POINT: None

RECOMMENDED COVERAGE:  
300 to 500 sq. ft. per gallon, per  
coat, depending on the type of  
surface and porosity.

DRYING TIME@70F&50%RH

To touch: 1/2 to 1 hour

To recoat: 1 to 2 hours

Foot traffic: 3 to 4 hours

Vehicle traffic: 72 hours

Drying times are influenced by  
ambient temperature and relative  
humidity.

CLEANUP: Water

## USES, FEATURES & BENEFITS

Anvil UltraSeal Concrete Floor & Driveway Sealer is specially formulated using styrene acrylic resins for use on unpainted horizontal concrete and asphalt surfaces such as driveways, garage floors, patios, walkways, decks and sidewalks. It is low odor, water reducible and non-flammable. UltraSeal provides a hard satin gloss finish that is water resistance. UltraSeal Concrete Floor & Driveway Sealer exhibits good resistance to most solvents and some chemicals, as well as oil and gasoline spills. Anvil UltraSeal is a high resin formula for bare horizontal concrete surfaces, but NOT for use on wood, brick pavers, stamped concrete, epoxy or polyurethane coatings. Brush, roller or spray applications can be successfully achieved with UltraSeal #1330.

## DIRECTIONS FOR USE AND SURFACE PREPARATION

Remove all dirt, efflorescence, grease, oil, waxes, silicone products and other foreign material that would interfere with the adhesion of the sealer. Uncoated smooth steel troweled concrete floors (surfaces with no porosity) must be totally cured, etched, neutralized, rinsed and cleaned for proper adhesion and durability of the sealer. A properly prepared surface will have the feel of 120 grit sandpaper.

## ULTRASEAL CONCRETE FLOOR & DRIVEWAY SEALER APPLICATION

Hand stir product thoroughly before application. Should be applied in thin multiple coats by brush, roller or spray. Avoid heavy application resulting in runs, ponding or puddling. Allow two hours drying time between coats. If relative humidity is high (> 80 percent), allow an extra period of drying time between coats. Two thin coats are recommended depending on the surface being coated and the gloss desired. Some surfaces such as inclined driveways, garages, patios, steps, etc. may require a slip resistant additive for safety. Add Anvil #9102 Skid Resistant Additive to the final coat of UltraSeal. This product should not be used in place of a nonskid finish. Coverage is approximately 300 to 500 square feet per gallon, per coat, depending on the type of surface and porosity. Do not dilute or apply if the threat of rain is imminent or if the air/surface temperature is expected to be below 50 degrees F within the first 24 hours of application. Allow 3 days (72 hours) for a full cure before allowing vehicle traffic on the

## 5-YEAR WARRANTY

This product is manufactured to rigid quality control specifications. Anvil Paints & Coatings, Inc. warrants to the original purchaser only, that UltraSeal Concrete Floor & Driveway Sealer, will be free of manufacturing defects for 5 years from date of purchase when applied in three coats, according to instructions as indicated. If purchaser discovers that UltraSeal Concrete Floor & Driveway Sealer has not performed as stated, promptly send written notification of this fact, along with proof of purchase, to Anvil Paints & Coatings, Inc., 1255 Starkey Road, Largo, FL 33771. If Anvil product is found to be defective, Anvil will provide the original purchaser with replacement sealer sufficient to repair the affected area. This remedy is the purchaser's Exclusive remedy.

## LIMITED WARRANTY AND LIMITATION OF REMEDIES

Anvil Paints & Coatings, Inc., disclaims all expressed warranties except those that appear above. Further, seller disclaims any implied warranty of merchantability of the goods or of the fitness of the goods for any purpose. To the extent allowed by law, any implied warrant of merchantability of fitness applicable to the sealer is limited to the five (5) year duration of the express warranty and is subject to all the terms and conditions of this limited warranty. Purchaser agrees that in no case shall Anvil Paints & Coatings, Inc. be liable for labor, incidental or consequential damages based upon any legal theory including, but not limited to, damages for loss of profits and/or injury to property or failure due to structural defects, acts of God or causes beyond our control, including the negligence of any person, and any other abuse or misuse of this product by purchaser.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE. ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED, WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID;** if you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**

VOC 221.1 grams/liter

Revised 5/2009 Supersedes all prior publications GRO



CLEAR SATIN GLOSS

NON-YELLOWING

STYRENE ACRYLIC RESINS

INTERIOR/EXTERIOR USE

EASY SOAP AND WATER CLEAN UP

LOW VOC

5 YEAR WARRANTY

USE ON UNPAINTED HORIZONTAL  
CONCRETE FLOORS & DRIVEWAYS

NON-FLAMMABLE

GOOD RESISTANCE TO MOST  
SOLVENTS