

BUILT TO PERFORM







We packed all the quality and durability you expect from Morgan into a compact design. LDX is perfect for inner city parcels, appliances and furniture deliveries.

STANDARD FEATURES



"R2" corner radius and front-end design, shown with optional LED lights



Our subframe, floor under-coating and unique mounting process, have set the industry standard



Bolt-on, black 10" step bumper

OPTIONS

FLOORING

• 1 1/8" Laminated Hardwood

BUMPER

• 5" Pooched Channel Bolt-on **Underride ICC Bumper**

ROOF ASSEMBLY

• .062" Translucent Fiberglass Roof

LIGHTING & REFLECTORS

- LED Exterior Lights to FMVSS108 Specifications
- 1 additional Interior Dome Light on Same Switch
- Conspicuity Tape on Sides/Rear

WALKRAMPS

 Availability Dependent on Body Length/Chassis Frame Width

LIFTGATE

- Waltco C-15RM 72" x 32" + 4"
- 1600 lb. Capacity
- Bolt-on Tuck-a-way Gate

SUBFRAME ASSEMBLY

- 4" Steel I-Beam Longrails
- 3" Steel I-Beam Cross Members on 16" Centers

FLOORING

· Pine Flooring

SIDEWALL ASSEMBLY

- .040" White Aluminum Skins
- Steel Z-Posts on 16" Centers

FRONT END ASSEMBLY

- .040" White Aluminum Skins
- "R2" Integrated Corner Radius
- 2" Extruded Aluminum Vertical Radii
- 2" Extruded Aluminum Top Radius with Cast Aluminum Corners

REAR FRAME ASSEMBLY

- Header Design with Rain Channel
- Painted (white) galvannealed Rear Frame
- Curbside and Roadside Grab Handles

REAR DOOR

· Overhead Roll-up Door

BUMPER

· Bolt-on Black 10" Pooched Step Bumper

ROOF ASSEMBLY

- .032" Aluminum Sheet
- Anti-Snag, Low Profile Roof Bows on 24" Centers

LIGHTING

- Incandescent Exterior Lights to FMVSS108 Specifications
- · Single Interior Dome Light with Switch in Cab



CARGO CONTROL

Sidewall E-Track Maximum 2 Rows Surface Mounted

Standard Settings

- 24" and 48"
- 30" and 60"

Optional settings starting at 18" center to floor on 6" increments

Front Wall E-Track Maximum 2 Rows Surface Mounted

Standard Settings

- 24" and 48"
- 30" and 60"

Optional settings starting at 18" center to floor on 6" increments

TIE RINGS Sidewall

 3 per Side Surface Mounted on Plywood at 42" from Floor

Front Wall

 2 Surface Mounted on Plywood at 42" from Floor

INTERIOR LINER & SCUFF - PLYWOOD

Front Wall

- 5.2 mm Luaun x 48" High
- 5.2 mm Luaun x Full Height Optional 101/2" Apitong Scuff over Luaun
- 3/8" Plywood x 48" High
- ³/₈" Plywood x Full Height Optional 10 ¹/₂" Apitong Scuff over Plywood
- 1/2" Plywood x 48" High
- 1/2" Plywood x Full Height Optional 10 1/2" Apitong Scuff over Plywood

Sidewall

- 5.2 mm Luaun x 48" High
- 5.2 mm Luaun x Full Height Optional 10¹/₂" Apitong Scuff over Luaun
- 3/8" Plywood x 48" High
- 3/8" Plywood x Full Height Optional 10 1/2" Apitong Scuff over Plywood

INTERIOR LINER & SCUFF - SLAT

Front Wall

- 79" 85" High Bodies
- 5 Slats Evenly Spaced
- 10 1/2" Apitong Scuff
- 91" High Bodies
- 6 Slats Evenly Spaced
- 10 1/2" Apitong Scuff

Sidewall

- 79" 85" High Bodies
- 5 Slats Evenly Spaced
- 10 ½" Apitong Scuff
- 91" High Bodies
- 6 Slats Evenly Spaced
- 10 $^{1}/_{2}$ " Apitong Scuff





Translucent roof - allows natural lighting to brighten cargo area



5" pooched underride bolt-on ICC bumper



Cargo Area* - Plywood liner, apitong scuff and tie rings



Cargo Area* - Slat liner (shown with optional 5" slats), and apitong scuff

DIMENSIONAL DATA

Sizes	Length					
Height	10′	12′	14′	15′	15′6″	16′
79"	•	•	•	•	•	•
85"			•		· .	•
91″	•	MET:	•	ML	•	•

^{*} All units 96" wide

Height & Width**						
Model	Overall Width	Interior Width	Exterior Height	Interior Height		
LDX-79	96"	92 – ⁷ / ₈ "	85 – ³ / ₈ "	79 – ¹ / ₈ "		
LDX-85	96"	92 – ⁷ / ₈ "	91 – ³ / ₈ "	85 – ¹ / ₈ "		
LDX-91	96"	92 – ⁷ / ₈ "	97 – ³ / ₈ "	91 – ¹ / ₈ "		

Length**			
Model	Exterior Length	Interior Length*	
10′	10′6 ¹ / ₂ ″	10′	
12′	12′6 ¹ / ₂ ″	12′	
14′	14′6 ¹ / ₂ ″	14′	
15′	15′6 ¹ / ₂ ″	15′	
15′6″	16′ ¹ / ₂ "	15′6″	
16′	16′6 ¹ / ₂ ″	16′	

Rear Roll-up Door Opening**				
Model	Opening Width	Opening Height		
LDX-79	88"	73″		
LDX-85	88"	79"		
LDX-91	88"	85"		

^{*} Inside front wall to inside rear door panel

Calculated Weight Chart**						
Model	10′	12′	14′	15′	15′6″	16′
LDX-79	1506	1717	2030	2130	2215	2244
LDX-85	1545	1758	2076	2179	2265	2291
LDX-91	1583	1800	2122	2228	2315	2339

Assumes mounted body with 3/8" side liner, 1/2" front liner, 1–3/8" pine flooring and a bolt-on step bumper



For More Information Contact Your Morgan Representative or Authorized Morgan Distributor

800-666-7426 **■** www.morgancorp.com

Follow us! **f l**





^{**}Note: All dimensions, weights and measurements specified herein are subject to change without notice and may vary depending on options selected. Please contact Morgan for measurements for your particular truck body and chassis specification.