



Anvil 1st Kote Drywall Primer & Equalizer

Interior Dry Wall
1815
Level 5

Tintable White

DESCRIPTION:

ANVIL 1ST KOTE PRIMER & EQUALIZER is a specially formulated interior dry wall primer that ensures the finish coat of paint will look it's best. **ANVIL 1ST KOTE PRIMER & EQUALIZER**, covers and primes the differences between the texture variations of gypsum board paper and joint compound finishes to a level 5 finish from a level 4 finish. It helps to equalize the porosity and surface texture differences found in new construction dry wall installations, typically called 'joint banding'. Forms a tight dry film, formulated with 'plating technology' which delivers excellent dry film hold out characteristics for satin and semi-gloss top coats. In production use ceilings can be left un-painted.

Uses:

ANVIL 1ST KOTE PRIMER & EQUALIZER is formulated for used on interior new construction drywall, or concrete surfaces. The prime finish produced by this product is excellent for walls in homes, hotels, motels, offices and apartments that require a uniform beautifully finished wall appearance. If used under wallpaper, a wallpaper primer or size should also be used. Not recommended for new plaster.

Surface Preparation:

Substrate must be clean, dry, sound and **PAINT READY**. Wall surfaces should be dry, free of dust, grime or other contaminants that could interfere with the bonding characteristics of **ANVIL 1ST KOTE PRIMER & EQUALIZER**. Product, air and surface temperatures must be maintained at a minimum of 50 F. New masonry must be allowed to cure for at least thirty (30) days. Repair any significant voids, cracks and fastener holes. Check all corner beads or exposed nail and screw heads that are likely to produce rust in the future and prime with a stain blocking metal primer. On walls stained from mildew, water, grease or other causes, a stain blocking primer should be applied to reduce flashing.

Coverage:

Coverage will vary greatly depending upon method of application, surface condition and technique of the applicator. A test application is recommended to determine actual coverage under specific job conditions. Average coverage is 300 to 500 square feet per gallon.

Application:

Apply by brush, roller or suitable airless spray unit at package consistency. The airless sprayer should be capable of delivering more than 3/4 gallon a minute. Remove all in-line filters. Use a 3/8" material hose and a 19 to 21 tip at 1700 to 2200 psi. Always work to a wet edge overlapping 1/4 to 1/2 the fan width. Varying orifice size, pressure and technique will have an effect on coverage rates. Roller application is best achieved using a 1/8" to 1/4" high quality nap roller designed for smooth surfaces. Maintain minimum air, product and surface temperature of 50F or above during application and until surface is dry, approximately 30 minutes to 1 hour under 77F/50% R.H.

TECHNICAL DATA:

Color: White, may be tinted.
up to 4oz. Universal Colorant
GENERIC TYPE: Vinyl Acrylic

GLOSS: Matte

SOLID CONTENT:

BY WIEGHT: 47.50
BY VOLUME: 29.08

%PIGMENT BY WEIGHT: 41.0
%VEHICLE BY WEIGHT: 6.50

VISCOSITY: 108 Ku

WEIGHT PER GALLON: 11.31 lbs.

RECOMMEDNED COVERAGE:
300 to 500 square feet per gallon

DRYING TIME @ 77 F, 50% RH:
Touch—1/2 to 1 hour
Top coat—2 hours

CLEANUP: Clean all equipment immediately after use with warm soapy water.

THINNING: Not recommended

AVAILABLE IN 1 AND 5 GALLON PAILS

VOC: 93.2 grams/liter

Revised 1-09 Supersedes all prior publications
GRO

Page 1 of 2

WARNING! WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! IRRITANT! HARMFUL IF SWALLOWED. IF TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID; if you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.